

FT

PROFESSIONAL LINE
COLD

Excellent efficiency

ALBERTI[®]
INTERNATIONAL

•Delayed Total Stop device



Dotazione Standard:

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo detergente in bassa pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Serbatoio detergente
- Valvola di regolazione pressione

Standard Equipment:

- H./P. hose mt 10
- Gun+Lance
- Low pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Detergent tank
- Pressure regulation valve



FT	120/10	170/13	150/15	200/15	150/21	200/21	250/15
Pressure	120 bar	170 bar	150 bar	200 bar	150 bar	200 bar	250 bar
Water delivery	600l/h	780l/h	900l/h	900l/h	1260l/h	900l/h	900l/h
Motor Revolution	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Power Supply	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
Motor Power	3 HP	5,5 HP	5,5 HP	7,5 HP	7,5 HP	10 HP	10 HP
Dimensions mm	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760
Tank Capacity	16lt	16lt	16lt	16lt	16lt	16lt	16lt
Weight	52 kg	56 Kg	56 Kg	60 Kg	60 Kg	64 Kg	64 Kg