

• **Delayed Total Stop device**

*Resistant stainless-steel structure*

**Dotazione Standard:**

- Tubo A/P mt 10
- Pistola+Lancia
- Dispositivo detergente in bassa pressione
- Pompa alta pressione con testata in ottone e pistoni in ceramica
- Valvola di regolazione pressione

**Standard Equipment:**

- H./P. hose mt 10
- Gun+Lance
- Low pressure chemical device
- High pressure pump with brass head and ceramic pistons
- Pressure regulation valve



<b>FLEXI SB</b>	<b>120/10</b>	<b>170/13</b>	<b>150/15</b>	<b>200/15</b>	<b>150/21</b>	<b>200/21</b>	<b>250/15</b>
<b>Pressure</b>	120 bar	170 bar	150 bar	200 bar	150 bar	200 bar	250 bar
<b>Water delivery</b>	600l/h	780l/h	900l/h	900l/h	1260l/h	1260l/h	900l/h
<b>Motor Revolution</b>	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm	1450 rpm
<b>Power Supply</b>	230V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz	400V-50Hz
<b>Motor Power</b>	3 HP	5,5HP	5,5HP	7,5HP	7,5HP	10 HP	10 HP
<b>Dimensions mm</b>	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760	480x760x760
<b>Weight</b>	52 Kg	56 Kg	56 Kg	60 Kg	60 Kg	64 Kg	64 Kg